15" SIGNATURE SERIES BEER DISPENSER

HP15TS-3 | 15" INDOOR MODEL **HP15TO-3** | 15" OUTDOOR MODEL













Dispensing Head Detail

GENERAL SIGNATURE SERIES FEATURES

- Zero-clearance hinging allows for abutment with surrounding cabinetry
- Best in Class 525 Btu commercial-grade compressor
- Front-vented, RAPIDcool forced-air refrigeration system
- Commercial-grade stainless steel interior and exterior
- Industry Exclusive convertible door design allows all doors the ability to be converted to wood overlay from stainless steel
- Industry Exclusive adjustable, full-extension pull-out shelves (drawer models and beer dispenser excluded)

- State-of-the-art digital control module
- Optional door locks (factory installed)
- Indoor and outdoor models available
- Also available 15" Refrigerator, Beverage Center, Wine Reserve and Clear Ice Maker
- 2.8 cubic feet of capacity
- Industry Best Three Year Warranty plus additional three years on sealed system

HP15TS-3/TO-3 FEATURES

- Available with solid stainless steel door or solid wood overlay door
- Comes standard with Perlick's industry exclusive 650SS flow control faucet
- Stores (1) 1/6 barrels
- Complete, self-contained beer system
- · Portable drainer; no plumbing required
- Low profile coupler for "D" system keg valves included
- Beer Dispenser temperature 33°- 42°F



(1) 1/6 barrel

Form No.HP15T-3 Rev. 01.15.2016

PRODUCT SPECIFICATIONS

Overall Width	14-7/8" (37.78 cm.)
Overall Height	34-1/4" (86.96 cm.)
Overall Depth	24" (60.96 cm.)
Opening Width	15" (38.1 cm.)
Opening Height	34-3/8" (87.31 cm.)
Opening Depth	24" (60.96 cm.)
Refrigerated Volume	2.8 cu. ft.
Door Swing Clearance	16" (40.64 cm.) minimum
Electrical	115V, 60Hz., 1 Phase, 2.3 amps
Plumbing	None Required
	000 114/1 /
Annual Energy Usage	280 kWh/yr

50" [1270] Area in which electrical outlet must be located 5¹/₁₆" [129] Power cord 6-5/8" [168] off floor.* $6\frac{1}{4}$ "[159] 18³/₁₆"[461] 1 3/8[32]" 11"[279]-Min. clearance from 11\bigg/{8}"[302] a corner to * - Leg leveler can add 3/4" [19] to these dimensions when fully extended. acheive 90° door swing. 90° Swing required for 15¹⁵/₁₆" [405] pull-out shelf 1%"[35] 24"[611] Min clearance clearance. for door swing Value may (with $\pm 1/16$ " tolerance) Value may change change due to a with a wood overlay door. custom pull. 14 / [378] 18³⁄₁₆"[461] -1¹⁵/₁₆"[49] -11"[279]-15/8 [42]-15/8"[42] 0 0 0 0 0 0 269/16"[674] 213/8"[543] 21%"[543] 26⁹/₁₆"[674] *34⁵/₁₆"[872] 3½"[89] $3\frac{1}{2}$ "[89] 1 *3 7/8" [100] **-**11⁷⁄₈"[302]-

INDOOR MODELS

OUTDOOR MODELS

Solid stainless steel door, hinge left

Solid wood overlay door, hinge left

Solid stainless steel door, hinge left

Solid wood overlay door, hinge left

HP15TS-3-1L*

HP15TS-3-2L*

HP15TO-3-1L*

HP15TO-3-2L*

* Also available hinge right

Form No.HP15T-3 Rev. 01.15.2016